

CARVER

by **Blanchon**
GROUP

CARSOL

Restorative oil

- ✓ Extraordinary maintenance and repair oil for oiled hardwood floors
- ✓ Quick drying
- ✓ Available in different colors

Code SO8202

CARSOL is a natural oil- and resin-based product. Specifically developed for the extraordinary care of oil-treated hardwood flooring, CARSOL penetrates deep down to regenerate the effects of the original treatment. CARSOL also restores the wear-damaged layer of oil on the surface.

The dual action of CARSOL, on the surface and deep down, extends the lifetime of PRIMOL and GREENOL PLUS treatments.

CARSOL is available in different colors (see color chart in the catalog).



APPLICATION

PREPARING THE SURFACE FOR TREATMENT

- Carefully clean the surface using our DETEROL wood soap (see technical data sheet).
- Leave the clean surface to dry naturally.
- Shake the can of CARSOL well before applying to allow the adequate dispersion of the flattening matter and any pigments.

APPLICATION CYCLE

- Apply a **very fine coat** of CARSOL, according to the recommended coverage, using a cloth or pad to the whole surface being treated. It is necessary to **rub the surface well** to help CARSOL to penetrate into the wood pores.
- 1-2 hours after application, polish the floor with a soft felt pad.

NOTICE

- Shake the can well before applying the product
- Before applying the product, wait for the surface being treated to reach a room temperature of at least +15°C.
- It is necessary to remember that the gram weight and drying times will depend on the type and the condition of the wood being treated. Higher absorption capacities of wood mean greater product weight and faster surface drying times.
- Never smoke during application and ventilate the area thoroughly.
- **Applying overly thick coats can cause problems in the drying process, especially in joint and knot areas.**
- Once the treatment has been completed, the floor can be cautiously walked on after 2-3 hours. **It is advisable to avoid any type of washing for the first 4-5 days.** After this period, the floor is ready for normal wear and maintenance.
- **Rinse used rags and paper soaked in product in water before disposal to prevent spontaneous combustion.**

TECHNICAL DATA

(based on room temperature of +23°C and 65% of relative air humidity)

Appearance of clear version	Opalescent brown liquid
Appearance of coloured version	Coloured liquid
Viscosity	14" F4 ± 1 " F4
Specific weight	0.82 ± 0.01
Surface drying	2-3 h
Complete drying	4-5 days
Average yield	30-60 m ² /l
Tool cleaning	DILUENTE LINOLUX / DILUENTE LAVAGGIO

If the original unopened container is stored in a cool and dry place, the product will keep for at least 12 months.

N.B.: The information contained in this technical data sheet is correct to the best of our knowledge and experience. Since the conditions of use are beyond our control, no warranty is given or implied.